Hidden Markov Models

Tapas Kanungo

Center for Automation Research

University of Maryland

Web: www.cfar.umd.edu/~kanungo

Email: kanungo@cfar.umd.edu

Outline

1. Markov models
2. Hidden Markov models
3. Forward/Backward algorithm
4. Viterbi algorithm
5. Baum-Welch estimation algorithm

Markov Models

- **Observable states:**

$$1, 2, \ldots, N$$

- **Observed sequence:**

$$q_1, q_2, \ldots, q_t, \ldots, q_T$$

- **First order Markov assumption:**

$$P(q_t = j | q_{t-1} = i, q_{t-2} = k, \ldots) = P(q_t = j | q_{t-1} = i)$$

- **Stationarity:**

$$P(q_t = j | q_{t-1} = i) = P(q_{t+l} = j | q_{t+l-1} = i)$$

Markov Models

- **State transition matrix** A :

$$A = \begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1j} & \cdots & a_{1N} \\ a_{21} & a_{22} & \cdots & a_{2j} & \cdots & a_{2N} \\ \vdots & \vdots & \cdots & \vdots & \cdots & \vdots \\ a_{i1} & a_{i2} & \cdots & a_{ij} & \cdots & a_{iN} \\ \vdots & \vdots & \cdots & \vdots & \cdots & \vdots \\ a_{N1} & a_{N2} & \cdots & a_{Nj} & \cdots & a_{NN} \end{bmatrix}$$

where

$$a_{ij} = P(q_t = j | q_{t-1} = i) \qquad 1 \leq i, j, \leq N$$

- **Constraints on** a_{ij} :

$$\begin{aligned} a_{ij} &\geq 0, & \forall i, j \\ \sum_{j=1}^{N} a_{ij} &= 1, & \forall i \end{aligned}$$

Markov Models: Example

- **States:**
  1. **Rainy** (R)
  2. **Cloudy** (C)
  3. **Sunny** (S)
- **State transition probability matrix:**

$$A = \begin{bmatrix} 0.4 & 0.3 & 0.3 \\ 0.2 & 0.6 & 0.2 \\ 0.1 & 0.1 & 0.8 \end{bmatrix}$$

- **Compute the probability of observing $SSRRSCS$ given that today is S.**

Markov Models: Example

Basic conditional probability rule:

$$P(A, B) = P(A|B)P(B)$$

The Markov chain rule:

$$\begin{aligned}
&P(q_1, q_2, \ldots, q_T) \\
&\quad = P(q_T|q_1, q_2, \ldots, q_{T-1})P(q_1, q_2, \ldots, q_{T-1}) \\
&\quad = P(q_T|q_{T-1})P(q_1, q_2, \ldots, q_{T-1}) \\
&\quad = P(q_T|q_{T-1})P(q_{T-1}|q_{T-2})P(q_1, q_2, \ldots, q_{T-2}) \\
&\quad = P(q_T|q_{T-1})P(q_{T-1}|q_{T-2}) \cdots P(q_2|q_1)P(q_1)
\end{aligned}$$

Markov Models: Example

- **Observation sequence** O :

$$O = (S, S, S, R, R, S, C, S)$$

- **Using the chain rule we get:**

$$\begin{aligned}
& P(O|model) \\
&= P(S, S, S, R, R, S, C, S|model) \\
&= P(S)P(S|S)P(S|S)P(R|S)P(R|R) \times \\
&\quad P(S|R)P(C|S)P(S|C) \\
&= \pi_3 a_{33} a_{33} a_{31} a_{11} a_{13} a_{32} a_{23} \\
&= (1)(0.8)^2(0.1)(0.4)(0.3)(0.1)(0.2) \\
&= 1.536 \times 10^{-4}
\end{aligned}$$

- **The prior probability** $\pi_i = P(q_1 = i)$

Markov Models: Example

- **What is the probability that the sequence remains in state i for exactly d time units?**

$$\begin{aligned} p_i(d) &= P(q_1 = i, q_2 = i, \ldots, q_d = i, q_{d+1} \neq i, \ldots) \\ &= \pi_i (a_{ii})^{d-1}(1 - a_{ii}) \end{aligned}$$

- **Exponential Markov chain duration density.**

- **What is the expected value of the duration d in state i?**

$$\begin{aligned} \bar{d}_i &= \sum_{d=1}^{\infty} d p_i(d) \\ &= \sum_{d=1}^{\infty} d (a_{ii})^{d-1}(1 - a_{ii}) \\ &= (1 - a_{ii}) \sum_{d=1}^{\infty} d (a_{ii})^{d-1} \\ &= (1 - a_{ii}) \frac{\partial}{\partial a_{ii}} \sum_{d=1}^{\infty} (a_{ii})^{d} \\ &= (1 - a_{ii}) \frac{\partial}{\partial a_{ii}} \left(\frac{a_{ii}}{1 - a_{ii}} \right) \\ &= \frac{1}{1 - a_{ii}} \end{aligned}$$

Markov Models: Example

- **Avg. number of consecutive sunny days =**

$$\frac{1}{1-a_{33}} = \frac{1}{1-0.8} = 5$$

- **Avg. number of consecutive cloudy days = 2.5**
- **Avg. number of consecutive rainy days = 1.67**

Hidden Markov Models

- States are not observable
- Observations are probabilistic functions of state
- State transitions are still probabilistic

Urn and Ball Model

- N urns containing colored balls
- M distinct colors of balls
- Each urn has a (possibly) different distribution of colors
- Sequence generation algorithm:
  1. Pick initial urn according to some random process.
  2. Randomly pick a ball from the urn and then replace it
  3. Select another urn according a random selection process associated with the urn
  4. Repeat steps 2 and 3

The Trellis


N
STATES
4
3
2
1
1
2
t-1
t
t+1
t+2
T-1
T
TIME
o 1
o 2
o t-1
o t
o t+1
o t+2
o T-1
o T
OBSERVATION

Elements of Hidden Markov Models

- N – **the number of hidden states**
- Q – **set of states** $Q = \{1, 2, \ldots, N\}$
- M – **the number of symbols**
- V – **set of symbols** $V = \{1, 2, \ldots, M\}$
- A – **the state-transition probability matrix.**

$$a_{ij} = P(q_{t+1} = j | q_t = i) \quad 1 \leq i, j, \leq N$$

- B – **Observation probability distribution:**

$$B_j(k) = P(o_t = k | q_t = j) \quad 1 \leq k \leq M$$

- π – **the initial state distribution:**

$$\pi_i = P(q_1 = i) \quad 1 \leq i \leq N$$

- λ – **the entire model** $\lambda = (A, B, \pi)$

Three Basic Problems

1. **Given observation $O = (o_1, o_2, \ldots, o_T)$ and model $\lambda = (A, B, \pi)$, efficiently compute $P(O|\lambda)$.**
   - **Hidden states complicate the evaluation**
   - **Given two models λ_1 and λ_2, this can be used to choose the better one.**
2. **Given observation $O = (o_1, o_2, \ldots, o_T)$ and model λ find the optimal state sequence $q = (q_1, q_2, \ldots, q_T)$.**
   - **Optimality criterion has to be decided (e.g. maximum likelihood)**
   - **"Explanation" for the data.**
3. **Given $O = (o_1, o_2, \ldots, o_T)$, estimate model parameters $\lambda = (A, B, \pi)$ that maximize $P(O|\lambda)$.**

Solution to Problem 1

- **Problem: Compute** $P(o_1, o_2, \ldots, o_T|\lambda)$
- **Algorithm:**
  - **Let** $q = (q_1, q_2, \ldots, q_T)$ **be a state sequence.**
  - **Assume the observations are independent:**

$$\begin{aligned} P(O|q,\lambda) &= \prod_{i=1}^{T} P(o_t|q_t,\lambda) \\ &= b_{q_1}(o_1)b_{q_2}(o_2)\cdots b_{q_T}(o_T) \end{aligned}$$

  - **Probability of a particular state sequence is:**

$$P(q|\lambda) = \pi_{q_1} a_{q_1 q_2} a_{q_2 q_3} \cdots a_{q_{T-1} q_T}$$

  - **Also,** $P(O, q|\lambda) = P(O|q,\lambda)P(q|\lambda)$
  - **Enumerate paths and sum probabilities:**

$$P(O|\lambda) = \sum_{q} P(O|q,\lambda)P(q|\lambda)$$

- N^T **state sequences and** $O(T)$ **calculations.**

  Complexity: $O(TN^T)$ **calculations.**

Forward Procedure: Intuition



Forward Algorithm

- **Define forward variable $\alpha_t(i)$ as:**

$$\alpha_t(i) = P(o_1, o_2, \ldots, o_t, q_t = i|\lambda)$$

- **$\alpha_t(i)$ is the probability of observing the partial sequence $(o_1, o_2 \ldots, o_t)$ such that the state q_t is i.**

- **Induction:**

  1. Initialization: $\alpha_1(i) = \pi_i b_i(o_1)$

  2. Induction:

$$\alpha_{t+1}(j) = \left[\sum_{i=1}^{N} \alpha_t(i) a_{ij}\right] b_j(o_{t+1})$$

  3. Termination:

$$P(O|\lambda) = \sum_{i=1}^{N} \alpha_T(i)$$

- **Complexity:** $O(N^2T)$.

Example

Consider the following coin-tossing experiment:

	State 1	State 2	State 3
P(H)	0.5	0.75	0.25
P(T)	0.5	0.25	0.75

– state-transition probabilities equal to 1/3

– initial state probabilities equal to 1/3

1. **You observe $O = (H, H, H, H, T, H, T, T, T, T)$. What state sequence, q, is most likely? What is the joint probability, $P(O, q|\lambda)$, of the observation sequence and the state sequence?**

2. **What is the probability that the observation sequence came entirely of state 1?**

3. Consider the observation sequence

$$\tilde{O} = (H, T, T, H, T, H, H, T, T, H).$$

How would your answers to parts 1 and 2 change?

4. If the state transition probabilities were:

$$A' = \begin{bmatrix} 0.9 & 0.45 & 0.45 \\ 0.05 & 0.1 & 0.45 \\ 0.05 & 0.45 & 0.1 \end{bmatrix},$$

how would the new model λ' change your answers to parts 1-3?

Backward Algorithm



Backward Algorithm

- **Define backward variable $\beta_t(i)$ as:**

$$\beta_t(i) = P(o_{t+1}, o_{t+2}, \ldots, o_T | q_t = i, \lambda)$$

- **$\beta_t(i)$ is the probability of observing the partial sequence $(o_{t+1}, o_{t+2} \ldots, o_T)$ such that the state q_t is i.**

- **Induction:**

  1. Initialization: $\beta_T(i) = 1$

  2. Induction:

$$\beta_t(i) = \sum_{j=1}^{N} a_{ij} b_j(o_{t+1}) \beta_{t+1}(j),$$
$$1 \leq i \leq N,$$
$$t = T-1, \ldots, 1$$

Solution to Problem 2

- **Choose the most likely path**
- **Find the path** $(q_1, q_t, \ldots, q_T)$ **that maximizes the likelihood:**

$$P(q_1, q_2, \ldots, q_T | O, \lambda)$$

- **Solution by Dynamic Programming**
- **Define:**

$$\delta_t(i) = \max_{q_1, q_2, \ldots, q_{t-1}} P(q_1, q_2, \ldots, q_t = i, o_1, o_2, \ldots, o_t | \lambda)$$

- $\delta_t(i)$ **is the highest prob. path ending in state** i
- **By induction we have:**

$$\delta_{t+1}(j) = \max_i [\delta_t(i) a_{ij}] \cdot b_j(o_{t+1})$$

Viterbi Algorithm



Viterbi Algorithm

- **Initialization:**

$$\begin{aligned}\delta_1(i) &= \pi_i b_i(o_1), \quad 1 \le i \le N \\ \psi_1(i) &= 0\end{aligned}$$

- **Recursion:**

$$\begin{aligned}\delta_t(j) &= \max_{1\le i\le N}[\delta_{t-1}(i)a_{ij}]b_j(o_t) \\ \psi_t(j) &= \arg\max_{1\le i\le N}[\delta_{t-1}(i)a_{ij}] \\ & \qquad 2 \le t \le T, 1 \le j \le N\end{aligned}$$

- **Termination:**

$$\begin{aligned}P^* &= \max_{1\le i\le N}[\delta_T(i)] \\ q_T^* &= \arg\max_{1\le i\le N}[\delta_T(i)]\end{aligned}$$

- **Path (state sequence) backtracking:**

$$q_t^* = \psi_{t+1}(q_{t+1}^*), \quad t = T-1, T-2, \ldots, 1$$

Solution to Problem 3

- **Estimate $\lambda = (A, B, \pi)$ to maximize $P(O|\lambda)$**
- **No analytic method because of complexity – iterative solution.**
- **Baum-Welch Algorithm:**
  1. **Let initial model be λ_0.**
  2. **Compute new λ based on λ_0 and observation O.**
  3. **If $\log P(O|\lambda) - \log P(O|\lambda_0) < DELTA$ stop.**
  4. **Else set $\lambda_0 \leftarrow \lambda$ and goto step 2.**

Baum-Welch: Preliminaries

- **Define $\xi(i,j)$ as the probability of being in state i at time t and in state j at time $t+1$.**

$$\begin{aligned}\xi(i,j) &= \frac{\alpha_t(i)a_{ij}b_j(o_{t+1})\beta_{t+1}(j)}{P(O|\lambda)} \\ &= \frac{\alpha_t(i)a_{ij}b_j(o_{t+1})\beta_{t+1}(j)}{\sum_{i=1}^{N}\sum_{j=1}^{N}\alpha_t(i)a_{ij}b_j(o_{t+1})\beta_{t+1}(j)}\end{aligned}$$

- **Define $\gamma_t(i)$ as probability of being in state i at time t, given the observation sequence.**

$$\gamma_t(i) = \sum_{j=1}^{N}\xi_t(i,j)$$

- **$\sum_{t=1}^{T}\gamma_t(i)$ is the expected number of times state i is visited.**

- **$\sum_{t=1}^{T-1}\xi_t(i,j)$ is the expected number of transitions from state i to state j.**

Baum-Welch: Update Rules

- $\bar{\pi}_i$ = **expected frequency in state** i **at time** $(t = 1)$ = $\gamma_1(i)$.
- $\bar{a}_{ij}$ = **(expected number of transition from state** i **to state** j**)/ (expected nubmer of transitions from state** i**):**

$$\bar{a}_{ij} = \frac{\Sigma\, \xi_t(i,j)}{\Sigma\, \gamma_t(i)}$$

- $\bar{b}_j(k)$ = **(expected number of times in state** j **and observing symbol** k**) / (expected number of times in state** j**:**

$$\bar{b}_j(k) = \frac{\Sigma_{t,o_t=k}\, \gamma_t(j)}{\Sigma_t\, \gamma(j)}$$

Properties

- Covariance of the estimated parameters
- Convergence rates

Types of HMM

- **Continuous density**
- **Ergodic**
- **State duration**

Implementation Issues

- **Scaling**
- **Initial parameters**
- **Multiple observation**

Comparison of HMMs

- **What is a natural distance function?**
- **If $\rho(\lambda_1, \lambda_2)$ is large, does it mean that the models are really different?**